

Omschrijving

De Proway PWH-4055 is een werkhandschoen uit de Tuff Serie. De Tuff serie is ideaal voor robuustere werkzaamheden. De PWH-4055 heeft een jersey liner. Een liner van jersey is sterk, duurzaam en door zijn elastisch vermogen heel comfortabel. De PWH-4055 heeft een blauwe 3/4 NBR coating en is voorzien van een tricot boord. Een NBR coating is slijtvast en is bestand tegen schuren. Deze coating zorgt voor een goede grip bij werken met zowel olie als vet. De 3/4 coating zorgt voor extra bescherming bij de vingers en zorgt in combinatie met de open handrug voor een goed ademend vermogen. Kies voor de Proway PWH-4055 en ervaar de robuuste kwaliteit van de Tuff serie.



Toepassingen

- Afvalverwerking
- Algemene werkzaamheden
- Bouw en constructie
- Industrie
- Infra grond-, weg- en waterbouw
- Metaalbewerking en plaatwerk
- Openbare werken
- Recycling
- Transport en logistiek



Download hier de gebruiksaanwijzing

Eigenschappen

Liner:	Jersey (katoen)
Liner kleur:	Beige
Gauge:	25G
Coating:	¾ Nitril
Coating kleur:	Blauw
Manchet:	Gebreide tricot boord

Productinformatie

Artikelnaam	Maat	Overlock kleur	VPE	Bundel
Tuff PWH-4055-10	10/XL	-	10 x 12 (120 paar)	12 paar

Certificering

Schuurweerstand: 4	EN 388:2016+A1:2018	2016/425	EN ISO 21420:2020
Snijweerstand: 1			
Scheurweerstand: 1			
Perforatieweerstand: 1	4111X	CAT II	
Snijweerstand (ISO 13997): X			

De prestaties zijn gemeten op de palm van de handschoen. 'X' geeft aan dat de handschoen niet is onderworpen aan de test of dat de testmethode niet geschikt lijkt te zijn voor het ontwerp of het materiaal van de handschoen.

Meer informatie:

: +31(0)162312387
 : sales@hawedo.com
www.prowayprotection.com



Hawedo B.V.
Prinses Margrietstraat 36
5104 AE Dongen Nederland

Description

The Proway PWH-4055 is a work glove from the Tuff Series. The Tuff Series is ideal for more demanding tasks. The PWH-4055 features a jersey liner. A jersey liner is strong, durable and, thanks to its elasticity, very comfortable. The PWH-4055 has a blue 3/4 NBR coating and features a tricot cuff. An NBR coating is wear-resistant and abrasion-resistant. This coating ensures a good grip when working with both oil and grease. The 3/4 coating provides extra protection for the fingers and, in combination with the open back, ensures good breathability. Choose the Proway PWH-4055 and experience the robust quality of the Tuff series.



Applications

- Building and construction
- Civil engineering
- General activities
- Industry
- Metalworking and sheet metal work
- Public works
- Recycling
- Transport and logistics
- Waste disposal



Download the user instructions here

Features

Liner:	Jersey (cotton)
Liner colour:	Beige
Gauge:	25G
Coating:	¾ Nitrile
Coating colour:	Bleu
Cuff:	Ribbed knit

Product information

Article name	Size	Overlock colour	Packing	Bundle
Tuff PWH-4055-10	10/XL	-	10 x 12 (120 pair)	12 pair

Certification

Abrasion resistance: 4	EN 388:2016+A1:2018	2016/425	EN ISO 21420:2020
Blade cut resistance: 1			
Tear resistance: 1			
Puncture resistance: 1			
Cut resistance (ISO 13997): X	4111X	CAT II	

Performance is measured on the palm of the glove. 'X' indicates that the glove has not been submitted to the test or the test method does not appear to be suitable for the glove design or material.

More information:

: +31(0)162312387
 : sales@hawedo.com
www.prowayprotection.com



Hawedo B.V.
Prinses Margrietstraat 36
5104 AE Dongen Netherlands